

**MD003 Monocrete 140**

Declaration of Performance			
Place of Manufacture		Gaerwen Works	
Intended use		in walls, columns and partitions	
Essential Characteristics		Performance	Harmonised technical specification
Dimensions <sup>(1)</sup>	Length	440mm	EN 771-3:2013
	Width	140mm	
	Height	215mm	
	Tolerance category	D1	
Configuration <sup>(1)</sup>	Shape and features	NPD	
	Group according to EN 1996-1-1 (EC6)	GROUP II	
Compressive strength <sup>(1)</sup>	Mean Compressive strength	7.3 N/mm <sup>2</sup>	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability <sup>(1)</sup>		<0.8 mm/m	
Bond strength <sup>(1)</sup>	shear bond strength	0.15N/mm <sup>2</sup>	
	Flexural bond strength	NPD	
Reaction to fire <sup>(2)</sup>		A1 (Commission Decision 2000/605/EC)	
Water absorption <sup>(3)</sup>		NPD	
Water vapour permeability <sup>(4)</sup>		5/15	
Direct airborne sound insulation <sup>(5)</sup> (in end conditions)/[Density and configuration]	Gross Density	1450 kg/m <sup>3</sup>	
	Configuration; dimensions and tolerances	See configuration	
Thermal resistance/or density and configuration <sup>(6)</sup>		0.215 m <sup>2</sup> /KW	
Durability against freeze/thaw		Pass	
Dangerous substances		NPD	
Signed on behalf of the manufacturer			Full name
Position		Quality Manager	Date 25 Mar 2013